

RC LT HIGH ACTIVES

PRODUCT Recycled lacquer solvent containing a high concentration of active solvents. DESCRIPTION

with methyl ethyl ketone as the primary active.

A high active solvent stream used in industrial applications for aggressive **USES AND**

cleaning and flushing of paint and coatings. **APPLICATIONS**

TYPICAL VALUES Active Solvents: 65.0% minimum

Methyl Ethyl Ketone: 45.0% minimum Water by KF: 1.0% maximum Color, Hazen (APHA): 50 maximum by LCS

NOTE The odor of this product varies with composition and the color will darken with

age from the date of manufacture.

PRECAUTIONS Product safety information and handling precautions are contained on the

product label and Safety Data Sheet (SDS).

READ AND UNDERSTAND LABEL AND SAFETY DATA SHEET BEFORE

PRODUCT USE.

RC0056 03-26-2025 Rev. 7

Hydrite Chemical Co. 17385 Golf Parkway Brookfield, WI P: 262-792-1450 E: info@hydrite.com www.hydrite.com

It is acknowledged that the application of the information contained herein may vary depending on the particular facts and circumstances and that future changes may render the information obsolete or inaccurate. Although we believe the information shown is accurate, Hydrite shall not be liable with respect to the application or use of any of the information. HYDRITE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MARKETABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ANY PRODUCT.